Volthium

Alimentez le futur
Powering the future

TECHNICAL SHEET
12 V 14 Ah



Volthium Energy inc. | T. 514.989.9586 | info@volthium.com | www.volthium.com

Volthium
Alimentez le futur
Powering the future

Before using your Volthium battery, please read the user manual and the datasheet specific to your battery.
You can find these documents by clicking on the following link: https://volthium.com/en/documents/
Any improper use of the product may void its warranty.
For any additional questions, please contact Volthium technical support.

ELECTRICAL SPECIFICATIONS	
Voltage	12.8 volt
Capacity	14 Ah
Capacity @ 10 A	84 min
Energy	179.2 Wh
Self-discharge	<3% per month
Maximum unit in series	N/A
Maximum unit in parallel	N/A

CHARGE SPECIFICATIONS	
Recommended charge current	1 A - 3A
Maximum charge current	10 A
Recommended charge voltage	14.2 V - 14.6 V (Bulk) | 13.6 V (Float)

DISCHARGE SPECIFICATIONS	
Recommended discharge current	5 A
BMS – Discharge disconnect voltage	10 V
BMS – Discharge reconnection voltage	10.8 V
Short circuit protection	Yes

TEMPERATURE SPECIFICATIONS	
Discharge temperature	From -30 to 60 °C
Charging temperature	From 0 to 45 °C


STORAGE SPECIFICATIONS	
Storage temperature	From -20 to 45 °C
Storage voltage	From 13.1 V to 13.3 V


COMMUNICATIONS SPECIFICATIONS	
Bluetooth	No
Communication ports	No
LCD screen	No
Volthium CAN Hub Communication (VE.CAN)	No

NUMBER OF CYCLES ACCORDING TO THE AVERAGE DISCHARGE % OF USE	
30% discharge	8200 < cycles
80% discharge	6000 < cycles
100% discharge	3500 < cycles

MECHANICAL SPECIFICATIONS	
Dimensions	151 X 98 X 97,1 mm | 5.95 X 3.86 X 3.81 po
Group / format	N/A
Weight	1.4kg / 3 lbs
Terminal Type	Tabs
Tightening torque on terminals	N/A
Ingress protection rating	IP20 (Against solid objects larger than 12 mm)

CERTIFICATIONS & DESIGN	
Design	N/A
Certifications	Cells : UL1642
Shipping classification	UN 3480 | CLASS 9
Cell type	Cylindric - LiFePO4 – 15 Ah 3.2 V - Grade A+


97.1


151
98

